

GalerieArt Plus Gloss Product Information



GalerieArt Plus Gloss is a coated fine paper available in sheets and reels for offset printing

Technical specifications

| Parameter | Standard | Unit | 90 | 100 | 115 | 130 | 150 | 170 | 200 | 250 | 300 | 350 |
|-------------------------|------------|--------------------|------|------|------|------|------|------|------|------|------|------|
| Basis weight | ISO 536 | g/m ² | 90 | 100 | 115 | 130 | 150 | 170 | 200 | 250 | 300 | 350 |
| CIE whiteness (D65/10°) | ISO 11475 | % | 124 | 125 | 126 | 126 | 126 | 126 | 126 | 126 | 126 | 126 |
| Opacity | ISO 2471 | % | 92 | 93 | 95 | 96 | 97,5 | 98 | 99 | 99,5 | 100 | 100 |
| Gloss TAPPI 75° | ISO 8254-1 | % | 65 | 65 | 65 | 65 | 65 | 65 | 65 | 65 | 65 | 65 |
| Bulk | ISO 534 | cm ³ /g | 0,78 | 0,78 | 0,79 | 0,80 | 0,81 | 0,82 | 0,83 | 0,94 | 0,94 | 0,98 |

Mill Certification

- ISO 9001** The quality of the manufacturing is managed according to the requirements of ISO 9001.
- ISO 14001** The environmental aspects of the mill are managed according to the requirements of ISO 14001.
- ISO 50001** The energy consumed and the emissions generated by the mill are managed according to ISO 50001.
- FSC™ C015022** The mills are both FSC and PEFC CoC certified, and all wood raw material originates from sustainable and controlled sources.
- PEFC™ C015022** The mills are both FSC and PEFC CoC certified, and all wood raw material originates from sustainable and controlled sources.
- OHSAS 18001** The health and safety of the mill employees are managed according to the requirements of OHSAS 18001.

Product Certification

- PEFC™ C015022** PEFC™ certification on request/subject to availability.
- FSC™ C015022** FSC™ certification on request/subject to availability.
- Food Contact** Only approved chemicals used, in compliance with BfR recommendation XXXVI 'Paper and Board for Food Contact'. GalerieArt Plus Gloss is suitable for direct contact with dry and fatty foodstuff.
- Toy Safety** Meets the purity requirements (heavy metal content) of EN 71-3 'Toy Safety', part 3 'Migration of certain elements' and part 9 'Organic chemical compounds'.
- Paper Profile** The key environmental parameters of the product are presented at the Paper Profile.
- Archivability** Archivability tested according to the requirements of DIN 6738, Lifespan class - LDK 24-85.
- ECF** Pulp is bleached without the use of elemental chlorine (ECF).
- Dry toner suitable** Dry toner: Suitable for dry toner.
- HP Indigo certified** HP Indigo: Certified for HP Indigo (115 – 350 g/m²).

Packaging of product complies with packaging and waste directive 94/62/EC (article 11). GalerieArt Plus Gloss is fully recyclable.

Target production values · Regional variations in specifications may apply; please contact your local Sales office for more information. Updated: 03.12.2019.
For the complete version of this datasheet please visit: www.sappiandyou.sappi.com